

Collection: Bliss 5.0	<b>PACKAGING</b>
Plank Size: 9" x 60" nom	
Gauge: 5.0mm (0.098")	
Backing Layer: 2mm Anchor Back™	
Finish: RQ® Protect	
Wear-layer: 22mil   0.55mm	
Bevel: Square Edge	
Gloss: Matte	
Embossing: Real Grain+	
Installation: All Grades and Levels	
Warranty: 25-Year Residential/10-Year Commercial	

**PACKAGING**

PCS / CTN: 6  
 SQFT / CTN: 22.28  
 CTNs / PLT: 48  
 PLTs /CAN: 21



**LOOSE LAY** FOR COMMERCIAL AND LIGHT INDUSTRY | **PUR** POLYURETHANE REINFORCEMENT | PRODUCT STANDARD: **ISO 10582**

**Technical Data**

CERTIFICATION & CLASSIFICATION	STANDARD	BLISS 5.0
Type of Floor Covering	ISO 10582	Luxury Vinyl Tile
CE Certification	EN 14041	Yes
Classification	EN ISO 10874	Commercial: 32   Light Industrial: 42

TECHNICAL CHARACTERISTICS	STANDARD	BLISS 5.0
Total Thickness	EN ISO 2436 (EN 428)	5.0 mm
Wear Layer Thickness	EN ISO 24340 (EN 429)	0.55 mm / 22 MIL
Surface Treatment	UV TREATED	PUR
Mass per Unit Area	EN ISO 23997 (EN 430)	9590 G/M <sup>2</sup>
Wear Layer Binder Content	ISO 10582	Type I
Form of Delivery	EN ISO 24342 (EN 427) PLANKS BOX	9" x 60" nom   6 Planks/Carton = 22.28 SF 230 x 1500 mm   6 Planks / Carton = 2.07 m <sup>2</sup>

TECHNICAL PERFORMANCE	STANDARD	BLISS 5.0
Dimensional Stability	EN ISO 23999 (EN 434)	≤ 0.20%
Reaction to Fire	EN 13501-1	Class BFL-S1
Residual Indentation	EN ISO 24343-1 (EN 433)	≤ 0.10 mm
Wear Resistance	EN 660-1	Group T
Castor Chair	EN ISO 4918 (EN 425)	No Damage
Curl Resultant to Heat	EN ISO 23999 (EN 434)	≤ 2 mm
Light Fastness	EN ISO 105-B02	≥ Grade 6
Resistance to Stain	EN 438	Grade 5
Resistance to Chemicals	EN ISO 26987 (EN 423)	Good Resistance
Slip Resistance	DIN 51130   EN 13893	R10   Class DS
Flexibility	ISO 24344	20 mm
Impact Sound improvement	ISO 717-2	ΔLw = 19 dB



This product is FloorScore® Certified and has thus been found to comply with the volatile organic compound emissions criteria of the California Section 01350 standard. FloorScore® Certification can also be used as an alternative path to obtaining LEED EQ 4.3 credit.



ISO 9001  
 ISO 14001  
 ISO 18001



PARAMOUNT FLOORING  
 www.ParamountFlooring.com



PHONE: 800-325-2625 FAX: 888-505-7383 WWW: herregan.com